


7676-73

Steel wire ropes. Locked conveying wire rope with
two layers of V-shaped wire, one layer of Z-wire and type TK core. Dimensions
12 5100, 12 5200

01.01.75

1.

1+6+12, 1+6+12+18 1+6+12+18+24.



2.

| | | | | | | | | | | | | | , (), , / 2 (/ 2) | | | | | | | | |
|------|-----|----|-----|----|------|---|----|------|---|----|------|---------|-------------------------|------------------|------------------|------------------|------------------|------------------|------------------|--|--|
| | | | | 1- | | | 2- | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | 100 | | | | | | | | |
| | | | | | | | | | | | | | | 1180 (120) | 1270 (130) | 1370 (140) | 1470 (150) | 1570 (160) | 1670 (170) | | |
| 50,0 | 3,6 | 19 | 5 | 18 | 17,8 | 5 | 24 | 19,2 | 6 | 24 | 30,8 | 1713,80 | 1469,51 | 2010 (205500) | 2180 (222500) | 2345 (239500) | 2515 (257000) | 2685 (274000) | 2850 (291000) | | |
| 52,0 | 4,0 | 19 | 5 | 19 | 17,8 | 5 | 26 | 19,2 | 6 | 25 | 30,8 | 1846,16 | 1582,83 | 2170 (221500) | 2350 (240000) | 2525 (258000) | 2705 (276500) | 2890 (295000) | 3070 (313500) | | |
| 54,0 | 4,4 | 19 | 5 | 20 | 19,0 | 5 | 27 | 19,2 | 6 | 26 | 30,8 | 1988,10 | 1704,37 | 2335 (238500) | 2525 (258000) | 2720 (278000) | 2920 (298000) | 3115 (318000) | 3305 (337500) | | |
| 55,0 | 3,4 | 37 | 4,5 | 21 | 17,2 | 5 | 27 | 19,2 | 6 | 26 | 30,8 | 2016,33 | 1728,06 | 2365 (241500) | 2565 (262000) | 2760 (282000) | 2955 (302000) | 3160 (322500) | 3355 (342500) | | |
| 60,0 | 4,1 | 37 | 4,5 | 24 | 17,2 | 5 | 30 | 20,1 | 6 | 28 | 32,3 | 2408,69 | 2063,60 | 2830 (289000) | 3065 (313000) | 3300 (337000) | 3535 (361000) | 3770 (385000) | 4005 (409000) | | |
| 65,0 | 3J | 6i | 4,5 | 26 | 18,3 | 5 | 33 | 20,1 | 6 | 30 | 32,3 | 2763,97 | 2367,31 | 3245 (331500) | 3515 (359000) | 3785 (386500) | 4060 (414500) | 4330 (442000) | 4600 (469500) | | |
| 70,0 | 4,3 | 61 | 4,5 | 30 | 18,3 | 5 | 33 | 22,5 | 6 | 37 | 28,5 | 3231,84 | 2767,12 | 3795 (387500) | 4115 (420000) | 4425 (452000) | 4745 (484500) | 5065 (517000) | 5380 (549000) | | |

1, (, . 2).

2,

3,

1370 / 2 (140 / 2)

01,01,91.

60,0 , l,

1270 / 2 (130 / 2):

60, - 0 7*76-75

(, , 1,2),

.3 7676-73

3. — , , , , , , -
18899.

1.

2.

15.06.73 1484

3.

7676-55

4.

-

18899-73

3

5.

4-93

-

(4-94)

6.

1, 2,

1985 .,

1989 . (6-85,

3-90)